

Electro-mechanical Assembly Press UFM 12/200/240

Article No.: 374012



The electro-mechanical assembly presses are designed for heavy duty applications in automatic assembly lines or manual loaded stations. Following components are part of the unit: robust mechanic with AC-servomotor, ball screw or threaded spindle for transfer the rotation into a linear movement, integrated force transducer measuring force directly and control unit.

Main functions	Nominal load	+/- 12 kN
	Stroke	200 mm
	Nominal speed	240 mm/s
	Dwell time of nominal load	min. 4 s
	Weight	38,6 kg
	Max. tool weight	8 Kg
Force measuring	Integrated strain gauge	
	Characteristic value	1 mV / V
	Transducer accuracy (dismantled)	0,5%
	System accuracy	< 1,5%
	Resolution	12 Bit
	Smallest measuring step	3,22 N
	Amplifier / W*H*D	Al-diecast housing / 150*64*36 mm
	Output signal	+/- 10 VDC
	Protection class	IP 54
Distance measuring	Resolver	
	Resolution	0,1 µm
	Repeatability of positioning	< 0,01 mm
Drive	All-digital pulse-inverter with steady intermediate voltage	
	Type / W*H*D	SP1404 / (100*386*219 mm)
	Nominal unit capacity	2,2 kW
	Mains voltage	3 AC 380 V - 480 V, +/-10 %, 48-65 Hz
	Cable cross sectional – area Input / Output	1,5 / 1 mm ²
	Protection class	IP 20
	Weight	5 kG
	Recommended protection	IEC gG / 12 A
	Temperature range	- 10 ... + 50 °C
	Thermal power loss	97 W
Additional Inputs	1x Analog / 1x Incremental	11 Bit / Encoder (max. 410 kHz)
Interface PC		Ethernet / RS 485
PLC Interface (24 VDC)	Standard (Optional Link module)	3 I / 4 O (12 I / 12 O)
PLC fieldbus interface	Optional	Profibus, CANOpen, Interbus, DeviceNet

